SURFACE PRIMER WB Part A Date Prepared: 01-18-2021

Date Prepared: 01-18-2021 Page 1

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

-----

PRODUCT NAME: SURFACE PRIMER WB Part A FORMULA NUMBER: JH3720

RECOMMENDED USE: Epoxy

MFG'S NAME: IG Products

11 Old Dock Rd. Yaphank, NY 11980 (631)-247-0744

EMERGENCY TELEPHONE NO.: 1-800-332-3883

\_\_\_\_\_\_

SECTION 2: HAZARD IDENTIFICATION

-----

HMIS RATING:

Health = 1 Flammability = 1 Reactivity = 0 Protection = B

0=Insignificant 1=Slight 2=Moderate 3=Serious 4=Severe

Potential Health Effects

Eye Contact: May cause eye irritation and burns Skin Contact: May cause slight irritation to skin.

Inhalation: Vapors may cause headaches, nausea, dizziness and respiratory irritation.

Ingestion: May cause irritation, nausea, vomiting and diarrhea.

\_\_\_\_\_\_

SECTION 3: COMPOSITION/ INFORMATION ON INGREDIENTS

\_\_\_\_\_

Ingredients CAS # % Wt epoxy resin 25068-38-6 30 - 40 % water 7732-18-5 60 - 75 %

\_\_\_\_\_\_

SECTION 4: FIRST AID MEASURES

------

Description of First Aid Measures

General: If irritation or other symptoms occur or persist from any route of of exposure, remove the affected individual from the area: see a physician and get medical attention if symptoms occur.

Eye Contact: Flush immediately with large volumes of water for at least 15 mins. Get medical treatment.

Skin Contact: Wash well with Soap & Water.

Inhalation: Remove to fresh air. Give Oxygen if breathing is difficult.

Get medical attention.

Ingestion: Consult physician or Poison Control Center Immediately.

SURFACE PRIMER WB Part A

Page 2

-----

SECTION 5: FIRE FIGHTING MEASURES

\_\_\_\_\_\_

Flash Point Deg F - 480 Method Used - TCC

Flammability Limits Lel - N/A Uel - N/A

\_\_\_\_\_\_

## SECTION 6: ACCIDENTAL RELEASE MEASURES

\_\_\_\_\_\_

Spill or Leak Procedures

Spills - Absorb liquid on paper and pick up with shovel. Powders and cements may be swept up using dustless method. Waste Disposal Methods - Place in closed containers. Do not close containers tightly as gassing may develop in some products. Dispose of in an approved land fill in accordance with local and federal regulations.

This product, if disposed as shipped, is not a hazardous waste as specified in 40 CFR261.

\_\_\_\_\_\_

### SECTION 7: HANDLING AND STORAGE

------

Respiratory Protection - NIOSH approved organic vapor cartridge or respirator designed to remove combination of particulates and vapor where concentrations are encountered.

Ventilation - Local exhaust capable of minimizing vapor concentrations. Use with adequate ventilation.

Precautions to be taken in handling & storage - Practice reasonable care and cleanliness.

\_\_\_\_\_

# SECTION 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION

\_\_\_\_\_

Exposure Limits 8 hrs. TWA

Ingredients OSHA PEL ACGHI TLV epoxy resin \* not est water \* non haz \* non haz

Personal Protection

Eye Protection: Safety glasses with side shields.

Skin Protection: Wear impervious gloves to avoid repeated or prolonged skin contact.

Respiratory Protection: NIOSH/MSHA approved respirator if required for dusts while using mechanical abrasion during removal or where concentrations are encountered.

Engineering Controls

Ventilation: Local exhaust capable of minimizing vapor or dust concentrations.

SURFACE PRIMER WB Part A Page 3 SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point deg.F - 212 Weight\Gallon @77F- 8.93 lbs % volatile by vol.- 60 - 75% Vapor Pressure- 1 Vapor Density -Evaporation Rate - slower BuAc=1

SECTION 10: STABILITY AND REACTIVITY

\_\_\_\_\_\_

Stability - STABLE - Hazardous polymerization CANNOT occur.

Conditions to Avoid -Avoid elevated temperatures.

SECTION 11: TOXICOLOGICAL INFORMATION

\_\_\_\_\_\_

Potential Health Effects

Eye Contact: May cause eye irritation, pain, redness.

Skin Contact: May cause slight irritation to skin, redness.

Inhalation: Vapors may cause headaches, nausea, dizziness and respiratory irritation.

Ingestion: May cause irritation, nausea, vomiting and diarrhea.

SPECIAL DATA:

SURFACE PRIMER WB Part A Page 4 SECTION 12: ECOLOGICAL INFORMATION Mobility: Water Contaminating. Do not allow material to escape into waters, wastewater or soil. Persistance and degradability: Not inherently biodegradable. Taking into consideration the properties of several components, the product is estimated not to be readiliy biodegradable according to OECD classification. Toxicity: Material may be toxic to aquatic organisms as shipped. \_\_\_\_\_\_ SECTION 13: DISPOSAL CONSIDERATIONS \_\_\_\_\_\_ Do not dump into sewers, on the ground, or into any body of water. All disposal practices must be in compliance with all Federal, State and local laws and regulations. Waste Disposal Methods - Place in closed containers. Do not Dispose of in an approved land fill in accordance with local and federal regulations. This product, if disposed as shipped, is not a hazardous waste as specified in 40 CFR261. -----SECTION 14: TRANSPORT INFORMATION DOT Classification - Paint ( NOT REGULATED ) SECTION 15: REGULATORY INFORMATION SARA 313 Chemicals : None All the ingredients of this product are on the TSCA inventory list. All the ingredients in this product are listed on the Canadian DSL US federal regulations: This product is a 'hazardous chemical' as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200 \_\_\_\_\_\_ SECTION 16: OTHER INFORMATION \_\_\_\_\_\_ Prepared by: IG Products Date Printed: 01-18-2021 The Following is in leu of all warranties, expressed or implied: All information provided is based on testing and data believed to be accurate.

SURFACE PRIMER WB Part B Date Prepared: 01-18-2021

Page 1

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

\_\_\_\_\_\_

PRODUCT NAME : SURFACE PRIMER WB Part B FORMULA NUMBER : JH3730

RECOMMENDED USE: Epoxy Hardener

MFG'S NAME: IG Products

11 Old Dock Rd. Yaphank, NY 11980 (631) - 247 - 0744

EMERGENCY TELEPHONE NO.: 1-800-332-3883

SECTION 2: HAZARD IDENTIFICATION

\_\_\_\_\_\_

HMIS RATING:

Health = 2 Flammability = 1 Reactivity = 1 Protection = B

0=Insignificant 1=Slight 2=Moderate 3=Serious 4=Severe

Potential Health Effects

Eye Contact: May cause severe irritation and burns with corneal injury that may result in permanent impairment of vision, even blindness. Skin Contact: Contact may cause skin irritation, burns, dermatitis, swelling, local redness, allergic skin reactions and sensitization. Inhalation: Vapor from heated material or mists may cause serious adverse effects. Excessive exposure may cause severe irritation to upper respiratory tract and lungs

Ingestion: May cause irritation, nausea, vomiting and diarrhea and/or burns to the mouth and throat.

# SECTION 3: COMPOSITION/ INFORMATION ON INGREDIENTS

\_\_\_\_\_\_ Ingredients

CAS # % Wt
68609-07-4 20 - 30 %
107-98-2 10 - 20 %
7732-18-5 50 - 60 %
ine 112-57-2 < 2% polyamine polymer 1-methoxy-2-propanol tetraethylene pentamine

## SECTION 4: FIRST AID MEASURES

\_\_\_\_\_\_

Description of First Aid Measures

General: If irritation or other symptoms occur or persist from any route of of exposure, remove the affected individual from the area: see a physician and get medical attention if symptoms occur.

Eye Contact: Flush immediately with large volumes of water for at least 30 mins. Remove contact lenses after the first 5 minutes & continue washing for 30 mins. Obtain prompt medical attention.

Skin Contact: Wash well with soap & water, remove contaminated clothing. Inhalation: Remove to fresh air. Give Oxygen if breathing is difficult. Get medical attention.

Ingestion: Drink 1 or 2 glasses of water or milk to dilute. Do not induce vomiting. Do not give anything to person unless they are fully conscious. Consult physician or Poison Control Center Immediately.

SURFACE PRIMER WB Part B Page 2 ------SECTION 5: FIRE FIGHTING MEASURES \_\_\_\_\_\_ Flash Point Deg F - >200 Flammability Limits Method Used - TCC Lel - N/A Uel - N/A Extinguishing Media - Dry Chemical, Foam, or Carbon Dioxide. Water may be ineffective. Special Fire Fighting Procedures - Fight as volatile liquid fire. Use water to keep fire-exposed containers cool to reduce pressure. Unusual Fire and Explosion Hazards - Keep away from heat sparks and open flame. SECTION 6: ACCIDENTAL RELEASE MEASURES Spill or Leak Procedures Spills - Absorb liquid on paper and pick up with shovel. Powders and cements may be swept up using dustless method. Waste Disposal Methods - Place in closed containers. Do not close containers tightly as gassing may develop in some products. Dispose of in an approved land fill in accordance with local and federal regulations. This product, if disposed as shipped, is not a hazardous waste as specified in 40 CFR261. \_\_\_\_\_\_ SECTION 7: HANDLING AND STORAGE Respiratory Protection - NIOSH approved organic vapor cartridge or respirator designed to remove combination of particulates and vapor in the absence of adequate ventilation or confined areas. Ventilation - Local exhaust recommended when appropriate to control employee exposure. Protective Gloves - Impervious gloves Eye Protection - Chemical Splash Goggles Other - Eye Wash Precautions to be taken in handling and storage - Practice reasonable care and cleanliness. Store material in cool dry location away from heat, sparks and open flame. Other - Avoid gross contamination of skin and wash with soap & water promptly. \_\_\_\_\_\_ SECTION 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION Exposure Limits 8 hrs. TWA \* not establishd \* not establishd 100 ppm \* non haz \* non haz Ingredients polyamine polymer 1-methoxy-2-propanol water \* not establshd \* not est tetraethylene pentamine

# Personal Protection

Eye Protection: Safety glasses with side shields or splashproof goggles. Respiratory Protection - NIOSH approved chemical/mechanical filters designed to remove a combination of particulates and vapor where concentrations are encountered.

Protective Gloves - Neoprene or Nitrile rubber gloves

Protective Gloves - Neoprene or Nitrile rubber gloves Other - Impervious apron and boots; eye wash.

# Engineering Controls

Ventilation: Local exhaust capable of minimizing vapor or dust concentrations.

SURFACE PRIMER WB Part B Page 3

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Boiling Point deg.F - 275 Weight\Gallon @77F- 8.53 lbs
Vapor Pressure- 3.8 mmHg % volatile by vol.- 60 - 75%
Vapor Density - heavier than air Evaporation Rate - slower
BuAc=1

\_\_\_\_\_\_

### SECTION 10: STABILITY AND REACTIVITY

Stability - STABLE - Hazardous polymerization CANNOT occur. Conditions to Avoid -Avoid contact with Acids and Oxidizing agents. Thermal Decompostion may produce carbon monoxide, carbon dioxide and oxides of nitrogen.

\_\_\_\_\_\_

# SECTION 11: TOXICOLOGICAL INFORMATION

\_\_\_\_\_\_

### Potential Health Effects

Eye Contact: May cause severe irritation and burns with corneal injury that may result in permanent impairment of vision, even blindness.

Skin Contact: Contact may cause skin irritation, burns, dermatitis, swelling, local redness, allergic skin reactions and sensitization.

Inhalation: Vapor from heated material or mists may cause serious adverse effects. Excessive exposure may cause severe irritation to upper respiratory tract and lungs

Ingestion: May cause irritation, nausea, vomiting and diarrhea and/or burns to the mouth and throat.

SPECIAL DATA:

SURFACE PRIMER WB Part B Page 4 SECTION 12: ECOLOGICAL INFORMATION Mobility: Water Contaminating. Do not allow material to escape into waters, wastewater or soil. Persistance and degradability: Not inherently biodegradable. Taking into consideration the properties of several components, the product is estimated not to be readiliy biodegradable according to OECD classification. Toxicity: Material may be toxic to aquatic organisms as shipped. -----SECTION 13: DISPOSAL CONSIDERATIONS \_\_\_\_\_\_ Do not dump into sewers, on the ground, or into any body of water. All disposal practices must be in compliance with all Federal, State and local laws and regulations. Waste Disposal Methods - Place in closed containers. Do not Dispose of in an approved land fill in accordance with local and federal regulations. This product, if disposed as shipped, is not a hazardous waste as specified in 40 CFR261. \_\_\_\_\_\_ SECTION 14: TRANSPORT INFORMATION \_\_\_\_\_\_ DOT Classification - Paint, ( Not Regulated ) SECTION 15: REGULATORY INFORMATION -----SARA 313 Chemicals : None All the ingredients of this product are on the TSCA inventory list. All the ingredients in this product are listed on the Canadian DSL US federal regulations: This product is a 'hazardous chemical' as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200 SECTION 16: OTHER INFORMATION \_\_\_\_\_\_ Prepared by: IG Products Date Printed: 01-18-2021 The Following is in leu of all warranties, expressed or implied: All information provided is based on testing and data believed to be accurate.