

SAFETY DATA SHEET

IG-2500 Gray PT A

Date Prepared: 01-18-2021

Page 1

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME :IG-2500 Gray PT A

FORMULA NUMBER : J45901

RECOMMENDED USE: Epoxy

MFG'S NAME: IG Products  
11Old Dock Rd  
Yaphank, NY 01980  
(631)-247-0744

EMERGENCY TELEPHONE NO.: 800-332-3883

SECTION 2: HAZARD IDENTIFICATION

HMIS RATING:

Health = 2 Flammability = 1 Reactivity = 0 Protection = B

0=Insignificant 1=Slight 2=Moderate 3=Serious 4=Severe

Potential Health Effects

Eye Contact: May cause eye irritation and burns

Skin Contact: May cause slight irritation to skin.

Inhalation: Vapors may cause headaches, nausea, dizziness and respiratory irritation.

Ingestion: May cause irritation, nausea, vomiting and diarrhea.

SECTION 3: COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredients	CAS #	% Wt
epoxy resin	25068-38-6	10 - 20 %
alkyl glycidyl ether	68609-97-2	< 3%
polyglycol epoxy resin	41638-13-5	< 3%
titanium dioxide	13463-67-7	< 1 %
alumino-silicate mineral	37244-96-5	20 - 30 %
aluminum oxide	1344-28-1	20 - 30 %
silica	14808-60-7	20 - 30 %

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: If irritation or other symptoms occur or persist from any route of exposure, remove the affected individual from the area: see a physician and get medical attention if symptoms occur.

Eye Contact: Flush immediately with large volumes of water for at least 15 mins. Get medical treatment.

Skin Contact: Wash well with Soap & Water.

Inhalation: Remove to fresh air. Give Oxygen if breathing is difficult. Get medical attention.

Ingestion: Consult physician or Poison Control Center Immediately.

SAFETY DATA SHEET

IG-2500 Gray PT A

Page 2

SECTION 5: FIRE FIGHTING MEASURES

Flash Point Deg F - 400	Flammability Limits
Method Used - TCC	Lel - N/A Uel - N/A

SECTION 6: ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures  
 Spills - Absorb liquid on paper and pick up with shovel.  
 Powders and cements may be swept up using dustless method.  
 Waste Disposal Methods - Place in closed containers. Do not close containers tightly as gassing may develop in some products. Dispose of in an approved land fill in accordance with local and federal regulations.  
 This product, if disposed as shipped, is not a hazardous waste as specified in 40 CFR261.

SECTION 7: HANDLING AND STORAGE

Respiratory Protection - NIOSH approved organic vapor cartridge or respirator designed to remove combination of particulates and vapor where concentrations are encountered.  
 Ventilation - Local exhaust capable of minimizing vapor concentrations. Use with adequate ventilation.  
 Precautions to be taken in handling & storage - Practice reasonable care and cleanliness.

SECTION 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Limits 8 hrs. TWA	OSHA PEL	ACGHI TLV
Ingredients		
epoxy resin	* not est	* not est
alkyl glycidyl ether	* not est	* not est
polyglycol epoxy resin	* not est	* not est
titanium dioxide	10 mg/m3 dust	10 mg/m3 dust
alumino-silicate mineral	10 mg/m3 dust	10 mg/m3 dust
aluminum oxide	5 mg/m3 dust	1 mg/m3 dust
crystalline silica (respirable)	0.3 mg/m3 dust	0.025mg/m3 dust

Personal Protection  
 Eye Protection: Safety glasses with side shields.  
 Skin Protection: Wear impervious gloves to avoid repeated or prolonged skin contact.  
 Respiratory Protection: NIOSH/MSHA approved respirator if required for dusts while using mechanical abrasion during removal or where concentrations are encountered.

Engineering Controls  
 Ventilation: Local exhaust capable of minimizing vapor or dust concentrations.

SAFETY DATA SHEET

IG-2500 Gray PT A

Page 3

-----  
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES  
-----

Boiling Point deg.F - 350	Weight\Gallon @77F- 17.07 lbs
Vapor Pressure- 5.6mm/Hg	% volatile by vol.- less than 4%
Vapor Density - 3.6	Evaporation Rate - 0.7
	BuAc=1

-----

SECTION 10: STABILITY AND REACTIVITY  
-----

Stability - STABLE - Hazardous polymerization may occur.  
Conditions to Avoid -Avoid contact with Acids and Oxidizing agents.  
Thermal Decomposition may produce carbon monoxide, carbon dioxide and oxides of nitrogen.

-----

SECTION 11: TOXICOLOGICAL INFORMATION  
-----

Potential Health Effects

Eye Contact: May cause eye irritation, pain, redness.

Skin Contact: May cause slight irritation to skin, redness.

Inhalation: Vapors may cause headaches, nausea, dizziness and respiratory irritation.

Ingestion: May cause irritation, nausea, vomiting and diarrhea.

SPECIAL DATA:

The carbon black pigment in this product contains less than 0.1% polynuclear aromatic hydrocarbons (PAH) , some of which, in non-adsorbed form, have been found to be carcinogens in animal studies. Carbon Black has not been listed by the NTP or OSHA. NIOSH recommends that only carbon blacks with a PAH level greater than 0.1% be considered suspect carcinogens. The International Agency for Research on Cancer (IARC) classifies carbon black as a suspect human carcinogen based on animal studies. Since the carbon black is not present in respirable form and encapsulated in the coating no over exposure to airborne dusts is to be expected.

crystalline silica - inhaled in the form of quartz or cristobalite is carcinogenic to humans ( Group 1 ). Crystalline silica is known to cause silicosis by airborne inhalation. If the silica is encapsulated in the coating no exposure to airborne dusts is to be expected. However, during removal by mechanical abrasion, appropriate safety practices should be followed to prevent inhalation of airborne dusts.

SAFETY DATA SHEET

IG-2500 Gray PT A

Page 4

-----  
SECTION 12: ECOLOGICAL INFORMATION  
-----

Mobility: Water Contaminating.

Do not allow material to escape into waters, wastewater or soil.

Persistence and degradability: Not inherently biodegradable.

Taking into consideration the properties of several components, the product is estimated not to be readily biodegradable according to OECD classification.

Toxicity: Material may be toxic to aquatic organisms as shipped.  
-----

SECTION 13: DISPOSAL CONSIDERATIONS  
-----

Do not dump into sewers, on the ground, or into any body of water.

All disposal practices must be in compliance with all Federal, State and local laws and regulations.

Waste Disposal Methods - Place in closed containers. Do not

Dispose of in an approved land fill in accordance with local and federal regulations.

This product, if disposed as shipped, is not a hazardous waste as specified in 40 CFR261.  
-----

SECTION 14: TRANSPORT INFORMATION  
-----

DOT Classification - Paint ( NOT REGULATED )  
-----

SECTION 15: REGULATORY INFORMATION  
-----

SARA 313 Chemicals : None

All the ingredients of this product are on the TSCA inventory list.

All the ingredients in this product are listed on the Canadian DSL

US federal regulations: This product is a 'hazardous chemical' as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200  
-----

SECTION 16: OTHER INFORMATION  
-----

Prepared by: IG Products

Date Printed: 03-21-2015

The Following is in leu of all warranties, expressed or implied:

All information provided is based on testing and data believed to be accurate.

☐:

SAFETY DATA SHEET

IG-2500 Hardener

Date Prepared: 01-18-2016

Page 1

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME : IG-2500 Hardener

FORMULA NUMBER : J45905

RECOMMENDED USE: Epoxy Hardener

MFG'S NAME: IG Products  
11 Old Dock Rd.  
Yaphank, NY 11980  
(631)-247-0744

EMERGENCY TELEPHONE NO.: 800-332-3883

SECTION 2: HAZARD IDENTIFICATION

HMS RATING:

Health = 3 Flammability = 1 Reactivity = 1 Protection = B

0=Insignificant 1=Slight 2=Moderate 3=Serious 4=Severe

Potential Health Effects

Eye Contact: May cause severe irritation and burns with corneal injury that may result in permanent impairment of vision, even blindness.

Skin Contact: Contact may cause skin irritation, burns, dermatitis, swelling, local redness, allergic skin reactions and sensitization.

Inhalation: Vapor from heated material or mists may cause serious adverse effects. Excessive exposure may cause severe irritation to upper respiratory tract and lungs

Ingestion: May cause irritation, nausea, vomiting and diarrhea and/or burns to the mouth and throat.

SECTION 3: COMPOSITION/ INFORMATION ON INGREDIENTS

Ingredients	CAS #	% Wt
amidoamine resin	68443-08-3	30 - 40 %
fatty amidoamine resin	68991-84-4	40 - 50 %
trimethylhexamethyldiamin	25620-58-0	1 - 5 %
amorphous silica	67762-90-7	5 - 10 %

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: If irritation or other symptoms occur or persist from any route of exposure, remove the affected individual from the area: see a physician and get medical attention if symptoms occur.

Eye Contact: Flush immediately with large volumes of water for at least 30 mins. Remove contact lenses after the first 5 minutes & continue washing for 30 mins. Obtain prompt medical attention.

Skin Contact: Wash well with soap & water, remove contaminated clothing.

Inhalation: Remove to fresh air. Give Oxygen if breathing is difficult.

Get medical attention.

Ingestion: Drink 1 or 2 glasses of water or milk to dilute. Do not induce vomiting. Do not give anything to person unless they are fully conscious.

Consult physician or Poison Control Center Immediately.

SAFETY DATA SHEET

IG-2500 Hardener

Page 2

SECTION 5: FIRE FIGHTING MEASURES

Flash Point Deg F - >200  
Method Used - TCC  
Extinguishing Media - Dry Chemical, Foam, or Carbon Dioxide. Water may be ineffective.  
Special Fire Fighting Procedures - Fight as volatile liquid fire. Use water to keep fire-exposed containers cool to reduce pressure.  
Unusual Fire and Explosion Hazards - Keep away from heat sparks and open flame.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures  
Spills - Absorb liquid on paper and pick up with shovel.  
Powders and cements may be swept up using dustless method.  
Waste Disposal Methods - Place in closed containers. Do not close containers tightly as gassing may develop in some products. Dispose of in an approved land fill in accordance with local and federal regulations.  
This product, if disposed as shipped, is not a hazardous waste as specified in 40 CFR261.

SECTION 7: HANDLING AND STORAGE

Respiratory Protection - NIOSH approved organic vapor cartridge or respirator designed to remove combination of particulates and vapor in the absence of adequate ventilation or confined areas.  
Ventilation - Local exhaust recommended when appropriate to control employee exposure.  
Protective Gloves - Impervious gloves  
Eye Protection - Chemical Splash Goggles  
Other - Eye Wash  
Precautions to be taken in handling and storage - Practice reasonable care and cleanliness.  
Store material in cool dry location away from heat, sparks and open flame.  
Other - Avoid gross contamination of skin and wash with soap & water promptly.

SECTION 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION

Exposure Limits 8 hrs. TWA

Ingredients	OSHA PEL	ACGHI TLV
amidoamine resin	* not est	* not est
fatty amidoamine resin	* not est	* not est
trimethylhexamethyldiamin	* not est	* not est
amorphous silica	* non haz	* non haz

Personal Protection

Eye Protection: Safety glasses with side shields or splashproof goggles.  
Respiratory Protection - NIOSH approved chemical/mechanical filters designed to remove a combination of particulates and vapor where concentrations are encountered.  
Protective Gloves - Neoprene or Nitrile rubber gloves  
Other - Impervious apron and boots; eye wash.

Engineering Controls

Ventilation: Local exhaust capable of minimizing vapor or dust concentrations.

SAFETY DATA SHEET

IG-2500 Hardener

Page 3

-----  
SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES  
-----

Boiling Point deg.F - N/A	Weight\Gallon @77F- 8.5 lbs
Vapor Pressure- N/A	% volatile by vol.- None
Vapor Density - heavier than air	Evaporation Rate - N/A
	BuAc=1

-----  
SECTION 10: STABILITY AND REACTIVITY  
-----

Stability - STABLE - Hazardous polymerization CANNOT occur.  
Conditions to Avoid -Avoid contact with Acids and Oxidizing agents.  
Thermal Decomposition may produce carbon monoxide, carbon dioxide and oxides of nitrogen.

-----  
SECTION 11: TOXICOLOGICAL INFORMATION  
-----

Potential Health Effects

Eye Contact: May cause severe irritation and burns with corneal injury that may result in permanent impairment of vision, even blindness.

Skin Contact: Contact may cause skin irritation, burns, dermatitis, swelling, local redness, allergic skin reactions and sensitization.

Inhalation: Vapor from heated material or mists may cause serious adverse effects. Excessive exposure may cause severe irritation to upper respiratory tract and lungs

Ingestion: May cause irritation, nausea, vomiting and diarrhea and/or burns to the mouth and throat.

SPECIAL DATA:

SAFETY DATA SHEET

IG-2500 Hardener

Page 4

-----  
SECTION 12: ECOLOGICAL INFORMATION  
-----

Mobility: Water Contaminating.

Do not allow material to escape into waters, wastewater or soil.

Persistence and degradability: Not inherently biodegradable.

Taking into consideration the properties of several components, the product is estimated not to be readily biodegradable according to OECD classification.

Toxicity: Material may be toxic to aquatic organisms as shipped.  
-----

SECTION 13: DISPOSAL CONSIDERATIONS  
-----

Do not dump into sewers, on the ground, or into any body of water.

All disposal practices must be in compliance with all Federal, State and local laws and regulations.

Waste Disposal Methods - Place in closed containers. Do not dispose of in an approved land fill in accordance with local and federal regulations.

This product, if disposed as shipped, is not a hazardous waste as specified in 40 CFR261.  
-----

SECTION 14: TRANSPORT INFORMATION  
-----

DOT Classification - Paint, 8 ( Corrosive ), UN3066, III

Quart size or less ships Limited Quantity (Consumer Commodity).  
-----

SECTION 15: REGULATORY INFORMATION  
-----

SARA 313 Chemicals : None

All the ingredients of this product are on the TSCA inventory list.

All the ingredients in this product are listed on the Canadian DSL

US federal regulations: This product is a 'hazardous chemical' as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200  
-----

SECTION 16: OTHER INFORMATION  
-----

Prepared by: IG Products

Date Printed: 01-18-2021

The Following is in leu of all warranties, expressed or implied:

All information provided is based on testing and data believed to be accurate.

: